

# CABELEC® CA3842 CONDUCTIVE COMPOUND

### Product highlights

CABELEC CA3842 is an electrically conductive compound based on carbon black and a polypropylene copolymer. It has very good mechanical properties and can be easily processed on conventional molding equipment.

### Key applications

CABELEC CA3842 conductive compound is recommended for the manufacture of containers and specialized moldings. Typical areas of applications are electronics packaging, ammunition works, mines, petroleum plants, and other environments where it is important to mitigate the hazard of electrostatic discharge.



### Processing

#### Pre-drying

CABELEC CA3842 conductive compound absorbs moisture under normal storage conditions and this can result in surface blemishes on moldings. It is therefore advisable to dry the compound prior to use. Usually 2 - 3 hours in a drier at 90°C is sufficient time to reduce the moisture content to an acceptable level.

#### Injection molding

CABELEC CA3842 conductive compound can be processed on most types of injection molding machine. Low shear conditions are nevertheless strongly recommended in order to achieve good electrical conductivity. The precise processing conditions depend on the machinery, output rate and complexity of the injected part under consideration. As a general guide, the following injection molding temperatures have been used successfully:

- ◆ Barrel/nozzle: 170°C / 200°C
- ◆ Mold: 15°C

#### Mold design

Generous gates are helpful for the molding of filled CABELEC as for other highly filled thermoplastics.

The information given in this section is provided as guidance only as different equipment could require different processing conditions to achieve the desired results.

# CABELEC® CA3842 CONDUCTIVE COMPOUND

TYPICAL PROPERTIES			
PROPERTY	TYPICAL VALUE	UNITS	TEST METHOD
Density @ 23°C	1090	kg/m <sup>3</sup>	ISO 1183
Hardness (15 second value)	66	Shore D	ISO 868
Heat Distortion Temperature @ 1.80 MPa	46	°C	ISO 75
Vicat Softening Point @ 10 N	148	°C	ISO 306
Mold Shrinkage	0.8 - 1.0	%	ASTM D955
Melt Flow Index (230°C/2.16 kg)	0.4	g/10 min	ISO 1133
Melt Flow Index (230°C/5.0 kg)	5	g/10 min	ISO 1133
Melt Flow Index (230°C/10.0 kg)	22	g/10 min	ISO 1133
Volume Resistivity	< 10 <sup>2</sup>	Ohm.cm	IEC 61340-2-3
Surface Resistivity	< 10 <sup>4</sup>	Ohm/sq	IEC 61340-2-3
Flexural Modulus	1500	MPa	ISO 178
Tensile Strength at Break	16	MPa	ISO 527
Tensile Strength at Yield	21	MPa	ISO 527
Elongation at Break	20	%	ISO 527
Notched Izod Impact @ 23°C	31	kJ/m <sup>2</sup>	ISO 180A
Flammability class (3mm)	HB 40	rating	UL94

The data in the table above are typical test values intended as guidance only and are not product specifications. Product specifications are available upon request from your Cabot representative.

For information on product-specific storage conditions, please refer to the applicable Safety Data Sheet (SDS) available from your Cabot representative or at [cabotcorp.com](http://cabotcorp.com).

The CABELEC name is a registered trademark of Cabot Corporation.

#### NORTH AMERICA

Cabot Plastics Canada  
707 Pierre Tremblay Boulevard  
Saint-Jean-sur-Richelieu  
QC, J2X 5G5  
Canada  
T +1 450 347 4371  
F +1 450 347 9936

#### SOUTH AMERICA

Cabot Brasil Indústria e  
Comércio Ltda.  
Rua do Paraíso 148 - 5º andar  
04103-000 São Paulo  
Brazil  
T +55 11 2144 6400  
F +55 11 3253 0051

#### EUROPE

SIA Cabot Latvia  
101 Mukusalas Street  
LV-1004 Riga  
Latvia  
T +371 670 50 900  
F +371 670 50 985

#### MIDDLE EAST/AFRICA

Cabot Specialty Chemicals  
Jebel Ali Free Zone  
LOB 15, Office 424, Dubai  
United Arab Emirates  
T +971 4 8871 800  
F +971 4 8871 801

#### ASIA PACIFIC

Cabot China Ltd.  
558 Shuangbai Road  
Minghang District  
Shanghai 201108  
China  
T +86 21 5175 8800  
F +86 21 6434 5532

#### JAPAN

Cabot Specialty Chemicals, Inc.  
Sumitomo Chiba-Daimon Bldg, 3F  
2-5-5 Shiba Daimon,  
Minato-ku, Tokyo 105-0012  
Japan  
T +81 6820 0255  
F +81 3 5425 4500

The data and conclusions contained herein are based on work believed to be reliable, however, Cabot cannot and does not guarantee that similar results and/or conclusions will be obtained by others. This information is provided as a convenience and for informational purposes only. No guarantee or warranty as to this information, or any product to which it relates, is given or implied. This information may contain inaccuracies, errors or omissions and CABOT DISCLAIMS ALL WARRANTIES EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AS TO (i) SUCH INFORMATION, (ii) ANY PRODUCT OR (iii) INTELLECTUAL PROPERTY INFRINGEMENT. In no event is Cabot responsible for, and Cabot does not accept and hereby disclaims liability for, any damages whatsoever in connection with the use of or reliance on this information or any product to which it relates.

# CABELEC® CA3842 CONDUCTIVE COMPOUND

## Product form and logistics

- ◆ Product form: pellets
- ◆ Regional availability: global
- ◆ Packaging options: 25 kg bags

For information on product-specific storage conditions, please refer to the applicable Safety Data Sheet (SDS) available from your Cabot representative or at [cabotcorp.com](http://cabotcorp.com).

The CABELEC name is a registered trademark of Cabot Corporation.

### NORTH AMERICA

Cabot Plastics Canada  
707 Pierre Tremblay Boulevard  
Saint-Jean-sur-Richelieu  
QC, J2X 5G5  
Canada  
T +1 450 347 4371  
F +1 450 347 9936

### SOUTH AMERICA

Cabot Brasil Industria e  
Comercio Ltda.  
Rua do Paraíso 148 - 5º andar  
04103-000 São Paulo  
Brazil  
T +55 11 2144 6400  
F +55 11 3253 0051

### EUROPE

SIA Cabot Latvia  
101 Mukusalas Street  
LV-1004 Riga  
Latvia  
T +371 670 50 900  
F +371 670 50 985

### MIDDLE EAST/AFRICA

Cabot Specialty Chemicals  
Jebel Ali Free Zone  
LOB 15, Office 424, Dubai  
United Arab Emirates  
T +971 4 8871 800  
F +971 4 8871 801

### ASIA PACIFIC

Cabot China Ltd.  
558 Shuangbai Road  
Minghang District  
Shanghai 201108  
China  
T +86 21 5175 8800  
F +86 21 6434 5532

### JAPAN

Cabot Specialty Chemicals, Inc.  
Sumitomo Chiba-Daimon Bldg, 3F  
2-5-5 Shiba Daimon,  
Minato-ku, Tokyo 105-0012  
Japan  
T +81 6820 0255  
F +81 3 5425 4500

The data and conclusions contained herein are based on work believed to be reliable, however, Cabot cannot and does not guarantee that similar results and/or conclusions will be obtained by others. This information is provided as a convenience and for informational purposes only. No guarantee or warranty as to this information, or any product to which it relates, is given or implied. This information may contain inaccuracies, errors or omissions and CABOT DISCLAIMS ALL WARRANTIES EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AS TO (i) SUCH INFORMATION, (ii) ANY PRODUCT OR (iii) INTELLECTUAL PROPERTY INFRINGEMENT. In no event is Cabot responsible for, and Cabot does not accept and hereby disclaims liability for, any damages whatsoever in connection with the use of or reliance on this information or any product to which it relates.